Product Information Packet: Model No: E3AC3006113B50S41100, Catalog No:E3AC3006113B50S41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 2,20kW, 3 phase, 958 RPM, D230/Y400V 50Hz, 112M Frame B5, 6 Poles, IC411

## Nameplate Specifications

Voltage	230/400 V
	23U/4UU V
Service Factor	1
Enclosure	Totally Enclosed Fan Cooled
Ambient Temperature	40 °C
Current	5.0 A
Duty	S1
Drive End Bearing Size	6306
UL	No
CE	Yes
Number of Speeds	1
	Service Factor  Enclosure  Ambient Temperature  Current  Duty  Drive End Bearing Size  UL  CE

## **Technical Specifications**

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	6	Rotation	Bi-Directional
Mounting	B5	Motor Orientation	Horizontal
Drive End Bearing	<b>Z</b> z	Opp Drive End Bearing	Zz
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	527.00 mm	Frame Length	230.00 mm
Shaft Diameter	28.000 mm	Shaft Extension	60 mm
Assembly/Box Mounting	Тор		
Outline Drawing	B5A04E8115001B01	Connection Drawing	SC-01-T-1v-1a

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:05/03/2023