Product Information Packet: Model No: E3AC3006317B35D41100, Catalog No:E3AC3006317B35D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 132,00kW, 3 phase, 990 RPM, D400/Y690V 50Hz, 315LC Frame B35, 6 Poles, IC411

Nameplate Specifications

Phase	3	Output HP	175.0 Hp
Output KW	132.0 kW	Voltage	400/690 V
Speed	990 rpm	Service Factor	1
Frame	315LC	Enclosure	Totally Enclosed Fan Cooled
Efficiency	95.5 %	Ambient Temperature	40 °C
Frequency	50 Hz	Power Factor	0.82
Duty	S1	Insulation Class	F
Drive End Bearing Size	6317	Opp Drive End Bearing Size	6316
UL	No	CSA	No
CE	Yes	IP Code	IP55
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	6	Rotation	Bi-Directional
Mounting	B35	Motor Orientation	Horizontal
Drive End Bearing	Zz C3	Opp Drive End Bearing	Zz C3
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	1707.00 mm	Frame Length	970.00 mm
Shaft Diameter	80.000 mm	Shaft Extension	170 mm
Assembly/Box Mounting	Тор		
Outline Drawing	B3A04E8310011D01	Connection Drawing	SC-01-T-1v-1a

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/10/2023