Product Information Packet: Model No: E3AC3006317B50D41100, Catalog No:E3AC3006317B50D41100 Made in Italy E3AC30 Series, General Purpose Low Voltage IEC motor IE3, Flameproof, 132,00kW, 3 phase, 990 RPM, D400/Y690V 50Hz, 315LC Frame B5, 6 Poles, IC411

## Nameplate Specifications

Phase	3	Output HP	175 Hp
Output KW	132.0 kW	Voltage	400/690 V
Speed	990 rpm	Service Factor	1
Frame	315LC	Enclosure	Totally Enclosed Fan Cooled
Efficiency	95.5 %	Ambient Temperature	40 °C
Frequency	50 Hz	Current	244.0 A
Power Factor	0.82	Duty	S1
Insulation Class	F	Drive End Bearing Size	6317
Opp Drive End Bearing Size	6316	UL	No
CSA	No	CE	Yes
IP Code	IP55	Number of Speeds	1

## **Technical Specifications**

	Starting Method	Direct On Line
6	Rotation	Bi-Directional
B5	Motor Orientation	Horizontal
Zz C3	Opp Drive End Bearing	Zz C3
Cast Iron	Shaft Type	Keyed
1707.00 mm	Frame Length	970.00 mm
80.000 mm	Shaft Extension	170 mm
Тор		
B5A04E8310011B01	Connection Drawing	SC-01-T-1v-1a
	B5 Zz C3 Cast Iron 1707.00 mm 80.000 mm Top	B5 Motor Orientation  Zz C3 Opp Drive End Bearing  Cast Iron Shaft Type  1707.00 mm Frame Length  80.000 mm Shaft Extension  Top

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:05/03/2023