PRODUCT INFORMATION PACKET



Model No: EX141173.00 Catalog No: EX141173.00

EX141173.00..7.5/5HP..1760/1470RPM.213TZ.TEFC.230/460//190/380V.3PH.60/50HZ.CONT.40C.1.15SF.RIGID..

.....





Nameplate Specifications

3	Output HP	7.50 & 5 Hp
5.6 & 3.7 kW	Voltage	230/460 & 190/380 V
1760 & 1470 rpm	Service Factor	1.15 & 1.15
213TZ	Enclosure	Totally Enclosed Fan Cooled
No Protection	Efficiency	89.5 & 89.5 %
40 °C	Frequency	60 & 50 Hz
20/10 & 17/8.5 A	Power Factor	78
Continuous	Insulation Class	F
В	KVA Code	Н
6307	Opp Drive End Bearing Size	6206
Recognized	CSA	Υ
N	IP Code	43
1		
	5.6 & 3.7 kW 1760 & 1470 rpm 213TZ No Protection 40 °C 20/10 & 17/8.5 A Continuous B 6307 Recognized	5.6 & 3.7 kW 1760 & 1470 rpm Service Factor 213TZ Enclosure No Protection Efficiency 40 °C Frequency 20/10 & 17/8.5 A Power Factor Continuous Insulation Class B KVA Code 6307 Opp Drive End Bearing Size Recognized CSA

Technical Specifications

Electrical Type	Squirrel Cage Inverter Rated	Starting Method	Line Or Inverter
Poles	4	Rotation	Reversible
Resistance Main	1.56 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	Single Special Extension	Assembly/Box Mounting	F1 ONLY
Inverter Load	CONSTANT 10:1		
Outline Drawing	609-0004	Connection Drawing	A-EE7308-LE

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023



