
## **PRODUCT INFORMATION PACKET**



Model No: G130000.00 Catalog No: G130000.00 BSOLETE - REPLACED BY 131519.00 - 3HP..1760RPM.182.DP./V.3PH.60HZ.CONT.NOT.40C.1.15SF.RIGID.GENER, L PURPOSE.C182T17DB33B





## Product Information Packet: Model No: G130000.00, Catalog No:G130000.00 OBSOLETE - REPLACED BY 131519.00 - 3HP..1760RPM.182.DP./V.3PH.60HZ.CONT.NOT.40C.1.15SF.RIGID.GENERAL PURPOSE.C182T17DB33B




## **Nameplate Specifications**

Phase	3	Output HP	3 & 2 Hp
Output KW	2.2 & 1.5 kW	Voltage	208-230/460 & 190/380 V
Speed	1760 & 1475 rpm	Service Factor	1.15 & 1.15
Frame	182T	Enclosure	Drip Proof
Thermal Protection	No Protection	Efficiency	86.5 & 87 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	9-8.8/4.4 & 7.8/3.9 A	Power Factor	73
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	К
Drive End Bearing Size	6206	Opp Drive End Bearing Size	6205
UL	Recognized	CSA	Y
CE	Υ	IP Code	22
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	4.85 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	035464-850	Connection Drawing	005010.01

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/23/2023



Uncontrolled Copy

