PRODUCT INFORMATION PACKET



Model No: KS14P020A40W35XSX Catalog No: AL08D4030MFAFTOAOO

14.0 Kw, Crane Duty Slipring Motors, 3 phase, 6 Pole, 415 V, S5 Duty, KS200L1 Frame, 40 CDF,

300 Start/Hr., TEFC





Regal and Marathon are trademarks of Regal Rexnord Corporation or one of its affiliated companies. ©2023 Regal Rexnord Corporation, All Rights Reserved. MC017097E




Nameplate Specifications

Output HP	18.80 Hp	Output KW	14.0 kW
Frequency	50 Hz	Voltage	415 V
Current	29.5 A	Speed	976 rpm
Phase	3	Duty	S 5
Frame	KS200L1	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	45 °C
Drive End Bearing Size	6312	Opp Drive End Bearing Size	6312
UL	No	CSA	No
CE	No	IP Code	55
CDF	40 %	Start/Hr	300
RA	32.5 A	RV	260 V
Insulation class Stator/Rotor	F/F	Temp. Rise Stator/Rotor	75/75 K
Stator Connection	Delta	Rotor Connection	Star
Efficiency Class	Standard		

Technical Specifications

Electrical Type	Slipring	Starting Method	Rotor resistance starter
Rotation	Bi-Directional	Mounting	IMB3
Motor Orientation	Horizontal	Drive End Bearing	Antifriction
Opp Drive End Bearing	Antifriction	Frame Material	Cast Iron/Fabricated
Shaft Type	Single Cylinder	Overall Length	947.00 mm
Frame Length	947.00 mm	Shaft Diameter	55.000 mm
Shaft Extension	110 mm	Assembly/Box Mounting	Тор
Rotor GD2	2.3 kg·m²	Pull Out Torque	4
Connection Drawing	DP2241	Outline Drawing	CM1383

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:03/06/2023



	FRAME	POLE	D(SHA	FT DIA)	E	GA	ı	F	G	D	G	;	Н		FIX	NG DI	MENSI	ONS	V	ша	40	ПΡ	40		DD.	D4			L1	LC1	TAPI	ER SHAF	T DIME	NSION	IS DET	TAILS (I	вотн)	
NO.			NOM.	TOL.			NOM.	TOL.	NOM.	TOL.	NOM.	TOL.	NOM.	TOL.	Α	В	С	CA		НА	AC	HD	AB	AA	BB	ВА		LC	L'	101	D1	D2	E1	E2	F1	H1	G1	Q
1	KS112M	4-8	28	+.009 004	60	31	8	+0 036	7	+0 090	24	+0 2	112	+0 -0.5	190	140	70	345	12	15	252	330	226	45	170	50	610	672.5	610	672.5	T28	M16x1.5	60	42	5	5	3	3
2	KS132M	4-8	38	+.018 +.002	80	41	10	+0	8	+0 090	33	+0 2	132	+0 -0.5	216	178	89	358	12	15	300	380	260	55	220	55	700	785	700	785	T38	M20x1.5	80	54	8	7	4	5
3	KS160M	4-8	42	+.018 +.002	110	45	12	+0 043	8	+0 090	37	+0 2	160	+0 -0.5	254	210	108	347	15	20	350	440	305	55	305	92.5	815	932	815	932	T42	M24x2	110	82 [©]	10	8	5	5
4	KS160L	4-8	42	+.018 +.002	110	45	12	+0 043	8	+0 090	37	+0 2	160	+0 -0.5	254	254	108	347	15	20	350	440	305	55	305	92.5	815	932	815	932	T42	M24x2	110	82 [@]	10	8	5	5
5	KS180L	4-8	48	+.018 +.002	110	51.5	14	+0 043	9	+0 090	42.5	+0 2	180	+0 -0.5	279	279	121	370	15	21	445	490	340	75	340 ^{@4}	85	875	990	875	990	T48	M30x2	110	82	12	8	5	5
6	KS200L	4-8	55	+.030 +.011	110	59	16	+0 052	10	+0 090	49	+0 2	200	+0 -0.5	318	305	133	399	19	25	450 [©]	545	400	89	365	95	947	1057	947 [©]	1057	T55	M36x3	110	82	14	9	5.5	5
·							-																															•

09	14.04.14	'E2' Dimension for Pt.No. 3 & 4 Changed to 82 was 87								
08	07.07.11	Unification of KS160 M&L Frame								
07	06.06.11	EARTHING TERMINAL INCORPORATED								ALL DII
06	19.07.10	'G' Dimn. for Pt.1 Changed to 24mm. was 27mm.			1(1)	marat	hon'	Marathon Elec		
05	14.12.07	COMPANY NAME AND LOGO CHANGED				gal Beloit Co				
04	05.05.06	'BB' Dimension for KS180 Frame was 394 mm. 'AC' Dimension for KS200 Frame was 494 mm. 'L' & 'L1' Dimension for KS20 Frame was 942 mm.			TITLE	OUTLINE	DIME	NSION DRAWI		
03	11.09.04	DRAWING GENERALLY REVISED						(KRANE MOT	JR	.)
В	10.11.97	'L' & 'L1' DIM. ALTERED (OLD 704) FOR PT.2	B.B.	S.B.	DRAWN B	B.BISWAS	23	3.07.96	T	DR/
А	19.04.97	'G' FOR PART 3 & 4 CHANGED	B.B.	S.B.		S.BHOWMICK		3.07.96		
REVISION	DATE	DETAIL OF REVISION	DONE BY	APPRVD	APPRVD. R	+	SIGN D	3.07.96 SCALE IF ANY ATE N.T.S	(CM