PRODUCT INFORMATION PACKET



Model No: LM16899 Catalog No: LM16899 OBSOLETE - 15,1800,TEFC,254TC,3/60/230/460





Nameplate Specifications

Phase	3	Output HP	15 & 10 Hp
Output KW	11.2 & 7.5 kW	Voltage	230/460 & 208/415 V
Speed	1770 & 1475 rpm	Service Factor	1.25 & 1.15
Frame	254TC	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	91 & 91 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	39/19.5 & 32/16 A	Power Factor	80
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	309	Opp Drive End Bearing Size	210
UL	Recognized	CSA	Υ
CE	Υ	IP Code	54
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	.575 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Cast Iron	
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	B-SS203152LN-1050	Connection Drawing	A-EE7308-LN	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/23/2023



