## PRODUCT INFORMATION PACKET



Model No: LM16825 Catalog No: LM16825 5,1800,TEFC,184TC,3/60/230/460





## Nameplate Specifications

3	Output HP	5 & 5 Hp
3.7 & 3.7 kW	Voltage	230/460 & 190-208/380-415 V
1755 & 1440 rpm	Service Factor	1.25 & 1.0
184TC	Enclosure	Totally Enclosed Fan Cooled
No Protection	Efficiency	90.2 & 87.5 %
40 °C	Frequency	60 & 50 Hz
12.4/6.2 & 15-14/7.5-7 A	Power Factor	83.5
Continuous	Insulation Class	F
В	KVA Code	J
207	Opp Drive End Bearing Size	205
Recognized	CSA	Υ
Υ	IP Code	43
1		
	3.7 & 3.7 kW  1755 & 1440 rpm  184TC  No Protection  40 °C  12.4/6.2 & 15-14/7.5-7 A  Continuous  B  207  Recognized	3.7 & 3.7 kW  1755 & 1440 rpm  Service Factor  184TC  Enclosure  No Protection  Efficiency  40 °C  Frequency  12.4/6.2 & 15-14/7.5-7 A  Power Factor  Continuous  Insulation Class  B  KVA Code  207  Opp Drive End Bearing Size  Recognized  CSA

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Resistance Main	2.62 Ohms	Mounting	Round
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Aluminum
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	B-SS601017LN-820	Connection Drawing	A-EE7308-LN

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/23/2023



