



Nameplate Specifications

Phase	3	Output HP	0.75 Hp
Output KW	.56 kW	Voltage	460 V
Speed	1165 rpm	Service Factor	1
Frame	182U	Enclosure	Totally Enclosed Non Ventilated
Thermal Protection	No Protection	Efficiency	81.5 %
Ambient Temperature	65 °C	Frequency	60 Hz
Current	1.3 A	Power Factor	68
Duty	Continuous	Insulation Class	F
Design Code	B	KVA Code	K
Drive End Bearing Size	206	Opp Drive End Bearing Size	205
UL	Recognized	CSA	Y
CE	Y	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line
Poles	6	Rotation	Reversible
Resistance Main	20.35 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	U	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	A-SS68737LN-575	Connection Drawing	A-EE7300-LN

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/06/2023