## PRODUCT INFORMATION PACKET



Model No: LM32750 Catalog No: LM32750

OBSOLETE - NO REPLACEMENT FOR ..40HP..3600RPM.286T.ODP.230/460V.3PH.60HZ.CONT.40C..RIGID.........

• • •






## Nameplate Specifications


Phase	3	Output HP	40 & 30 Hp
Output KW	30.0 & 22.4 kW	Voltage	230/460 & 190/380 V
Speed	3540 & 2945 rpm	Service Factor	1.25 & 1.15
Frame	286T	Enclosure	Drip Proof
Thermal Protection	No Protection	Efficiency	93.6 & 93.6 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	90/45 & 82/41 A	Power Factor	89
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	G
Drive End Bearing Size	6310	Opp Drive End Bearing Size	6209
UL	Recognized	CSA	Υ
CE	Υ	IP Code	12
Number of Speeds	1		

## **Technical Specifications**

Electrical Type	Squirrel Cage Induction Run	Starting Method	Wye Start Delta Run
Poles	2	Rotation	Reversible
Resistance Main	.182 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	Т	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	XF2D1SS1-1448	Connection Drawing	A-EE7308AA-LN

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023





ERROR: undefined

OFFENDING COMMAND: Pscrip

STACK: