PRODUCT INFORMATION PACKET



Model No: LM33263 Catalog No: LM33263

..5HP..3600RPM.184T.TEFC.230/460V.3PH.60HZ.GENERAL PURPOSE.40C..RIGID.....





Nameplate Specifications

Phase	3	Output HP	5 & 5 Hp
Output KW	3.7 & 3.7 kW	Voltage	230/460 & 190/380 V
Speed	3515 & 2910 rpm	Service Factor	1.25 & 1.25
Frame	184T	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	Thermostat	Efficiency	88.5 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	12/6 & 14/7 A	Power Factor	89
Duty	Continuous	Insulation Class	F
Design Code	A	KVA Code	К
Drive End Bearing Size	206	Opp Drive End Bearing Size	205
UL	Recognized	CSA	Υ
CE	Υ	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	2	Rotation	Reversible	
Resistance Main	2.32 Ohms	Mounting	Rigid Base	
Motor Orientation	Horizontal	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel	
Shaft Type	т	Assembly/Box Mounting	F1/F2 CAPABLE	
Outline Drawing	035465LN	Connection Drawing	05010.20LN	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023

