PRODUCT INFORMATION PACKET



Model No: LM34009 Catalog No: LM34009

..5HP..1800RPM.184T.TEFC.230/460V.3PH.60HZ.Cont.40C.1.25SF......






Nameplate Specifications

Phase	3	Output HP	5 & 5 Hp
Output KW	3.7 & 3.7 kW	Voltage	230/460 & 190-208/380-415 V
Speed	1755 & 1440 rpm	Service Factor	1.25 & 1.0
Frame	184TV	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Efficiency	90.2 & 87.5 %
Ambient Temperature	40 °C	Frequency	60 & 50 Hz
Current	12.4/6.2 & 15-14/7.5-7 A	Power Factor	83.5
Duty	Continuous	Insulation Class	F
Design Code	В	KVA Code	J
Drive End Bearing Size	6207	Opp Drive End Bearing Size	6205
UL	Recognized	CSA	Υ
CE	Υ	IP Code	43
Number of Speeds	1		

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Across The Line	
Poles	4	Rotation	Reversible	
Resistance Main	2.62 Ohms	Mounting	Rigid Base	
Motor Orientation	Shaft Up	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Aluminum	
Shaft Type	Т	Assembly/Box Mounting	W8	
Outline Drawing	B-SS601006LN-820	Connection Drawing	A-EE7308-LN	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023



184T

16.19

8.30

DIST LB

В

SS601006LN

12

