PRODUCT INFORMATION PACKET



Model No: LM80238

Catalog No: LM80238

Fire Pump Motor, 125 & 100 HP, 3 Ph, 60 & 50 Hz, 460 & 380-400 V, 3600 & 3000 RPM, 404TS Frame, DP



Regal and Leeson are trademarks of Regal Rexnord Corporation or one of its affiliated companies. ©2023 Regal Rexnord Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Phase	3	Output HP	125 & 100 Hp	
Output KW	93.0 & 75.0 kW	Voltage	460 & 380-400 V	
Speed	3575 & 2975 rpm	Service Factor	1.15 & 1.15	
Frame	404TS	Enclosure	Drip Proof	
Thermal Protection	No Protection	Efficiency	93.6 & 93 %	
Ambient Temperature	50 °C	Frequency	60 & 50 Hz	
Current	139 & 135-130 A	Power Factor	89	
Duty	Continuous	Insulation Class	F	
Design Code	В	KVA Code	F	
Drive End Bearing Size	6313	Opp Drive End Bearing Size	6313	
UL	No	CSA	Υ	
CE	Υ	IP Code	23	
Number of Speeds	1			

Technical Specifications

Electrical Type	Squirrel Cage Induction Run	Starting Method	Part Wdg Start & Wye Start Delta Run
Poles	2	Rotation	Reversible
Resistance Main	.07 Ohms	Mounting	Rigid Base
Motor Orientation	Horizontal	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Cast Iron
Shaft Type	тѕ	Overall Length	33.86 in
Frame Length	19.68 in	Shaft Diameter	2.125 in
Shaft Extension	4.25 in	Assembly/Box Mounting	F1/F2 CAPABLE
Outline Drawing	SS620752-404	Connection Drawing	EE7300BH

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/22/2023



