Product Information Packet: Model No: P327M2, Catalog No:P327M2 10 HP Close-Coupled Pump Motor, 1 phase, 3600 RPM, 230 V, 215JP Frame, ODP



Nameplate Specifications

| Output HP | 10 Hp | Output KW | 7.5 kW | |
|--------------------|------------|---------------------|-----------------|--|
| Frequency | 60 Hz | Voltage | 230 V | |
| Current | 37.5 A | Speed | 3510 rpm | |
| Service Factor | 1.15 | Phase | 1 | |
| Duty | Continuous | Insulation Class | F | |
| Frame | 215JP | Enclosure | Open Drip Proof | |
| Thermal Protection | No | Ambient Temperature | 40 °C | |
| UL | Recognized | CSA | Υ | |
| Number of Speeds | 1 | | | |

Technical Specifications

| Electrical Type | Capacitor Start Capacitor Run | Starting Method | Across The Line |
|-----------------------|-------------------------------|-------------------|------------------|
| Poles | 2 | Rotation | Counterclockwise |
| Mounting | Rigid Base | Drive End Bearing | Ball |
| Opp Drive End Bearing | Ball | Frame Material | Rolled Steel |
| Shaft Type | Keyed | Overall Length | 25.04 in |
| Frame Length | 12.40 in | Shaft Diameter | 1.750 in |
| Shaft Extension | 8.43 in | | |
| Connection Drawing | A-EE9048MF-CY | Outline Drawing | 037644CY |
| | | | |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/07/2021