

## Nameplate Specifications

Output HP	75 Hp	Output KW	55.0 kW
Frequency	50 Hz	Voltage	380 V
Current	104.9 A	Speed	1489 rpm
Service Factor	1	Phase	3
Efficiency	95.7 %	Power Factor	0.84
Duty	<b>S1</b>	Insulation Class	F
Frame	250M	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
Drive End Bearing Size	6314	Opp Drive End Bearing Size	6314
UL	No	CSA	No
CE	YES	IP Code	55
Number of Speeds	1	Efficiency Class	IE4
		-	

## **Technical Specifications**

Electrical Type	Squirrel Cage	Starting Method	Direct On Line	
Poles	4	Rotation	Bi-Directional	
Mounting	B5	Motor Orientation	Horizontal	
Drive End Bearing	С3	Opp Drive End Bearing	СЗ	
Frame Material	Cast Iron	Shaft Type	Keyed	
Overall Length	970 mm	Frame Length	425 mm	
Shaft Diameter	65 mm	Shaft Extension	140 mm	
Assembly/Box Mounting	Тор			
Outline Drawing	0225000396	Connection Drawing	8442000085	

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/01/2022