

Nameplate Specifications

| Output HP | 120 Hp | Output KW | 90.0 kW |
|------------------------|---------------|----------------------------|-----------------------------|
| Frequency | 50 Hz | Voltage | 380 V |
| Current | 158.2 A | Speed | 2982 rpm |
| Service Factor | 1 | Phase | 3 |
| Efficiency | 95.8 % | Power Factor | 0.91 |
| Duty | S1 | Insulation Class | F |
| Frame | 280M | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6314 | Opp Drive End Bearing Size | 6314 |
| UL | No | CSA | No |
| CE | YES | IP Code | 55 |
| Number of Speeds | 1 | Efficiency Class | IE4 |
| | | | |

Technical Specifications

| Electrical Type | Squirrel Cage | Starting Method | Direct On Line |
|-----------------------|---------------|-----------------------|----------------|
| Poles | 2 | Rotation | Bi-Directional |
| Mounting | V1 | Motor Orientation | Shaftdown |
| Drive End Bearing | СЗ | Opp Drive End Bearing | С3 |
| Frame Material | Cast Iron | Shaft Type | Keyed |
| Overall Length | 1246 mm | Frame Length | 600 mm |
| Shaft Diameter | 65 mm | Shaft Extension | 140 mm |
| Assembly/Box Mounting | Тор | | |
| Outline Drawing | 0228000588 | Connection Drawing | 8442000085 |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/01/2022