Product Information Packet: Model No: QCA1602A1121GAA001, Catalog No:QCA1602A1121GAA001 TerraMAX® Cast Iron Motor, 215 HP, 3 Ph, 50 Hz, 400 V, 1500 RPM, 315L Frame, TEFC

## marathon®

## Nameplate Specifications

Output HP	215 Нр	Output KW	160.0 kW
Frequency	50 Hz	Voltage	400 V
Current	276.1 A	Speed	1490 rpm
Service Factor	1	Phase	3
Efficiency	96.6 %	Power Factor	0.87
Duty	S1	Insulation Class	F
<b>F</b> arana	045	Freiseure	Tetally Friday of Fair Octobed
Frame	315L	Enclosure	Totally Enclosed Fan Cooled
Thermal Protection	No Protection	Ambient Temperature	40 °C
			-
Thermal Protection	No Protection	Ambient Temperature	40 °C
Thermal Protection Drive End Bearing Size	No Protection 6319	Ambient Temperature Opp Drive End Bearing Size	40 °C 6319

## **Technical Specifications**

Electrical Type	Squirrel Cage	Starting Method	Direct On Line
Poles	4	Rotation	Bi-Directional
Mounting	B5	Motor Orientation	Horizontal
Drive End Bearing	СЗ	Opp Drive End Bearing	СЗ
Frame Material	Cast Iron	Shaft Type	Keyed
Overall Length	1317 mm	Frame Length	840 mm
Shaft Diameter	80 mm	Shaft Extension	170 mm
Assembly/Box Mounting	Тор		
Outline Drawing	0231500897	Connection Drawing	8442000085

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 12/01/2022