

Nameplate Specifications

| Output HP | 120 Hp | Output KW | 90.0 kW |
|------------------------|---------------|----------------------------|-----------------------------|
| Frequency | 50 Hz | Voltage | 380 V |
| Current | 161.7 A | Speed | 2982 rpm |
| Service Factor | 1 | Phase | 3 |
| Efficiency | 95 % | Power Factor | 0.89 |
| Duty | S1 | Insulation Class | F |
| Frame | 280M | Enclosure | Totally Enclosed Fan Cooled |
| Thermal Protection | No Protection | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6314 | Opp Drive End Bearing Size | 6314 |
| UL | No | CSA | No |
| CE | Yes | IP Code | 55 |
| Number of Speeds | 1 | Efficiency Class | IE3 |
| | | | |

Technical Specifications

| Electrical Type | Squirrel Cage | Starting Method | Direct On Line | |
|-----------------------|---------------|-----------------------|----------------|--|
| Poles | 2 | Rotation | Bi-Directional | |
| Mounting | В3 | Motor Orientation | Horizontal | |
| Drive End Bearing | С3 | Opp Drive End Bearing | C3 | |
| Frame Material | Cast Iron | Shaft Type | Keyed | |
| Overall Length | 1111 mm | Frame Length | 600 mm | |
| Shaft Diameter | 65 mm | Shaft Extension | 140 mm | |
| Assembly/Box Mounting | R Side | | | |
| Outline Drawing | 0228001134 | Connection Drawing | 8442000085 | |
| | | | | |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:12/01/2022