

## Nameplate Specifications

| Output HP          | 10 Hp      | Output KW           | 7.5 kW     |  |
|--------------------|------------|---------------------|------------|--|
| Frequency          | 60 Hz      | Voltage             | 575 V      |  |
| Current            | 10.2 A     | Speed               | 1768 rpm   |  |
| Service Factor     | 1.15       | Phase               | 3          |  |
| Duty               | Continuous | Insulation Class    | F          |  |
| Frame              | 215T       | Enclosure           | Drip Proof |  |
| Thermal Protection | No         | Ambient Temperature | 40 °C      |  |
| UL                 | Recognized | CSA                 | Υ          |  |
| CE                 | Υ          | Number of Speeds    | 1          |  |
|                    |            |                     |            |  |

## **Technical Specifications**

| Electrical Type       | Three Phase | Starting Method   | Across The Line |
|-----------------------|-------------|-------------------|-----------------|
| Poles                 | 4           | Rotation          | Reversible      |
| Mounting              | Rigid Base  | Drive End Bearing | Ball            |
| Opp Drive End Bearing | Ball        | Frame Material    | Rolled Steel    |
| Shaft Type            | Т           | Overall Length    | 17.52 in        |
| Frame Length          | 11.30 in    | Shaft Diameter    | 1.375 in        |
| Shaft Extension       | 3.38 in     |                   |                 |
| Connection Drawing    | EE7300      | Outline Drawing   | SS620684        |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/12/2021